

PNEUMATIC SPIDERS

For Casing, Tubing and Drill Pipe

Designed for medium and heavy-duty operation, our Pneumatic Spider is one of the most versatile power slips available.

FEATURES:

- Heat-treated alloy steel is used throughout for longer service.
- All shafts are hardened alloy steel for longer service.
- Replaceable steel bushings are used for extended wear.
- All bushing are equipped with grease fittings.
- Spiders are equipped with manually operated safety latch which may be used to positively lock the slips in their set position.
- Slips will not release from tubing until it has been raised by the elevator.



SPECIFICATIONS

	MODEL "B"	MODEL "C"	MODEL "CHD"
HEIGHT	15.5"	16.5"	16.5"
BASE DIMENSION	14" × 17"	16.5" × 18.5"	16.5" × 18.5"
GATE OPENING	4.25"	5.75"	5.75"
BOWL OPENING	4.75" DIAMETER	6.5" DIAMETER	6.5" DIAMETER
TUBULAR RANGE	1.315" TO 3.5"	1.315" TO 5.5"	1.315" TO 5.5"
MAXIMUM LOAD CAPACITY	110,000 LBS	165,000 LBS	250,000 LBS

Contact us today!

Crown Houston
1617 Richey Road
Houston, Texas 77073
(281) 442-1339

Visit us on the Web at www.stewartandstevenson.com

SSLLC2007-03-042 ©2007 STEWART & STEVENSON

All data subject to change without notice. The information in this bulletin is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Stewart & Stevenson's control. Stewart & Stevenson disclaims any liability in connection with the use of this information, and does not warrant against infringement by reason of the use of any of its products in combination with other material or in any process. Stewart & Stevenson warrants only that the product complies with specifications agreed to in contracts of sale.



Building For The Next Century